Standard Features

INTERIOR

- Decorative Rods w/side Panels Main Living Areas
- 2" Blinds Throughout
- Shaw 25 oz. "New Wave" Carpet w/ 5# Rebond Pad
- Lux Congoleum No Wax Vinyl Flooring
- 8' Flat Ceilings Throughout
- Stipple Ceiling Finish
- Wall Coverings 3/8" Wall Board
- Ventilated Wire Shelving in Closets
- LED Recessed Can Lights T/O Except Baths
- CFL Bulbs Installed
- Ceiling Fan with Light Living Room
- 2" DuraCraft Flat Ceiling Cove, Door & Window Casing Throughout
- 32" 2-Panel White Interior Doors with 3 Mortised Hinges Bedrooms & Baths
- High Pressure Countertops-Throughout
- 4" Laminate Backsplash Throughout
- Foyer Linoleum
- Door Chime
- Pfister Metal Faucets Kitchen & Baths

KITCHEN

- 42" Raised Panel DuraCraft Overhead Cabinets
- Center Shelf Base Cabinets
- Refrigerator Overhead Cabinet
- MDF Stiles
- GFCI Receptacles
- Metal Drawer Guides
- Bank of Drawers (4)
- Cabinet Doorknobs & Drawer Pulls- Black
- Concealed Cabinet Door Hinges
- 8" Stainless Steel Double Bowl Kitchen Sink
- Frigidaire Appliances
 - 30" Free-Standing Electric Range Black
 - 18 CF Frost Free Refrigerator Black
- Window Over Kitchen Sink (where available)

BATHS

- 60" 1pc. Fiberglass Tub/Shower Bath 1 & Bath 2
- Porcelain Square Sinks Both Baths
- Elongated Commodes Both Baths
- Lighted Power Exhaust Fans Both Baths
- GFCI Receptacles
- Towel Bar & Tissue Holders Both Baths
- 3-Bulb Strip Bar Vanity Lights Both Baths
- Stile Framed Mirrors Both Baths

INSULATION

- Zone III Insulation
 - R-28 Blown Ceiling Insulation with Vapor Barrier
 - R-13 Fiberglass Insulation in Walls Single Section
 - R-19 Fiberglass Insulation in Walls Sections
 - R-11 Fiberglass Insulation in Floors Between I-Beams
 - R-19 Fiberglass Insulation Floors-Outside I-Beams

EXTERIOR

- Nominal 3/12 Roof Pitch
- OSB Exterior Sheathing
- 25 Year Tamko Fiberglass Shingle
- Ice and Water Shield
- Aluminum Fascia w/Vented Soffit
- 36"x80" Residential Fiberglass Front Door with Storm & Deadbolt – Storm Door Shipped Loose
- 36"x80" Residential Fiberglass Rear with Storm & Deadbolt – Storm Door Shipped Loose
- Exterior Light at Front & Rear Doors
- Double 4.5" Dutch Lap Vinyl Siding
- (1) Exterior Faucet
- (1) Exterior Recept
- Conduit Drop
- Single Hung Low E White Vinyl Windows No Grids
- 15" Raised Panel Shutters Door Side & H.E. Single Section
- 15" Raised Panel Shutters Door Side Sectionals
- Kwikset® Smart Key Locks & Hardware

UTILITIES

- Carrier Electric Furnace with Door
- 200 AMP Service Panel Box
- In-Line / Perimeter Floor Registers
- High/Low Return Air System (where available)
- 40 Gallon Electric Water Heater
- Water Heater Pan with Exterior Drain
- PEX Plumbing
- Wire & Plumb for Washer
- Wire & Vent for Dryer Installed
- Individual Water Shut Offs Throughout
- Recessed Whole House Shut Off
- Linked Smoke / CO Detectors in Main Living Areas and All Bedrooms
- Ecobee 3 "SMART" Thermostat

CONSTRUCTION

- Steel I-Beam Frame with Detachable Hitch
- 2"x6" Floor Joists 16" O.C. Single Section & Sectionals
- 2"x4" Exterior Walls 16" O.C. Single Section
- 2"x6" Exterior Walls 16" O.C. Sectionals
- 19/32" T&G OSB floor Decking Glued & Fastened
- 20 lb. Roof Load
- Roof Truss 24" O.C.
- 7/16" OSB Roof Sheathing
- Ridge Vent Roof Venting
- Metal In-Floor Crossovers Sectionals
- Exterior Door Supports, Front & Rear Doors
- All Exterior Penetrations Sealed
- Raised Siding Skirting Application